dalton technical fact sheet

Product name: Blotting Paper

Mill: Australian Paper - Shoalhaven

Country of origin: Australia

Web address: www.australianpaper.com.au

Technical Specifications

- ☐ Coated Paper
  - ☐ A1
  - ☐ A2+
  - ☐ A2
  - ☐ A3
- ☑ Archival Life
- ☑ ISO 9706 - Paper for documents Requirements for permanence
- ☑ PH Neutral
- ☑ ISO 9001 - Quality Management System
- ☐ FDA Approved
- ☑ High Bulk
- ☐ High Opacity
- ☐ Digital Print
- ☐ Inkjet Compatible
- ☐ Laser Guaranteed
- ☐ Laser Compatible
- ☐ Waterproof
- ☐ Special Inks Recommended

Traditionally used for absorbing excess ink when handwriting with ink pens. Today this sheet is used primarily in the manufacture of laboratory hand sheets when undertaking specific laboratory testing where absorbency properties are necessary. Blotting paper pH is in the range 7.5 to 10.0 as per the Australian and international standards for permanent papers.

It is not suitable for traditional printing processes.

	ISO STD	Unit of measure										
Nominal Weight		g/m2	135									
Burst		kPa	230									
Moisture		%	6.5									
Porosity		Sheffield	180									
Thickness		µm	255									

Last Updated: February 2009