



jac fluoro colours

Avery Dennison - Australia

- A matt Fluorescent Paper which exhibits good printability by a range of processes.
- Applications include warning or caution labels, high impact advertising, overdue correspondence, collection stickers and other eye-catching labels.

Technical information

Weight	80gsm
Thickness	83um

Print Carrier

Offset and Foil Stamping

Adhesive

ET9

ET9 is a permanent acrylic adhesive designed for paper stocks, which shows excellent adhesion to a wide range of surfaces including most grades of recycled cardboard and difficult plastic containers. Suitable for all automatic application equipment, ET9 has good die cutting, high speed stripping and low bleed characteristics.

Typical Physical Properties

Adhesion	FTM1	720 N/m
Tack°	FTM9	600 N/m
Min. Application Temp	5°C → +70°C	
Service Temp	-20°C → +100°C	

Release Liner

B90

A high wet strength woodfree kraft paper with good dimensional stability and flatness during processing, combined with resilience required for high speed die cutting operations.

Typical Physical Properties

Weight	87 g/m ²
Thickness	92 µm

Split

This paper has lengthwise incisions every 50mm. Bending the paper at any of these points allows the backing to be removed in pieces, enabling for quicker application and easier positioning of labels. Jac Split is dimensionally stable and an ideal backing for sheet stock, especially when labels are not die cut.